

## INTRODUCTION

The "1,200-foot" sand of the Baton Rouge area is a major source of fresh ground water in a five-parish area which includes East and West Baton Rouge, East and West Feliciana, and Pointe Coupee Parishes (hereinafter referred to as the Baton Rouge area) in southeastern Louisiana (fig. 1). In 2001, the "1,200-foot" sand was the fourth most heavily pumped aquifer of the 14 aquifers (fig. 2) underlying this area. In 2001, about 20.8 Mgal/d was withdrawn from the "1,200-foot" sand in the Baton Rouge area (fig. 3). Of this amount, about 55 percent was used for public supply, about 6 percent for power generation, and about 38 percent for industrial purposes (D.C. Dial, Capital Area Ground Water Conservation Commission, written commun., 2002). Most of the water, about 18.5 Mgal/d, was withdrawn in East Baton Rouge Parish (D.C. Dial, Capital Area Ground Water Conservation Commission, written commun., 2002). From 1990 to 2001, withdrawals from the "1,200-foot" sand increased by about 26 percent (from 16.6 to 20.8 Mgal/d, fig. 3) in the Baton Rouge area.

Pumpage from the "1,200-foot" sand has caused water-level declines in the Baton Rouge area (Meyer and Turcan, 1955, p. 54, 57). Also, previous studies have indicated the possibility that saltwater<sup>1</sup> encroachment (horizontal movement) into freshwater areas has occurred (Tomaszewski, 1996, p. 6; Whiteman, 1979, p. 41-42).

Additional knowledge about ground-water flow and effects of withdrawals on the "1,200-foot" sand of the Baton Rouge area is needed to assess ground-water-development potential and to protect the resource. To meet this need, the U.S. Geological Survey (USGS), in cooperation with the Capital Area Ground Water Conservation Commission (CAGWCC), began a study in 2000 to measure and document the current (2001) water levels in wells screened in the "1,200-foot" sand, construct a potentiometric-surface (water-levels) map, and to evaluate changes in the potentiometric surface.

This report presents data and maps that describe the potentiometric surface of the "1,200-foot" sand of the Baton Rouge area during the spring of 2001. Graphs of water levels in selected wells and water withdrawals from the "1,200-foot" sand are presented to show the historical changes in water levels and water use. The potentiometric-surface map illustrates the water levels and ground-water flow directions in the aquifer for spring 2001. Water-level and water-use data are on file at the USGS and CAGWCC offices in Baton Rouge, Louisiana.

## Description of Study Area

The study area (fig. 1) extends across about 2,000 mi<sup>2</sup> and includes East and West Baton Rouge, East and West Feliciana, and Pointe Coupee Parishes (Calhoun and Frois, 1997, p. 153). The City of Baton Rouge and several industrial facilities are located in the study area along the Mississippi River. The climate is generally warm and temperate with high humidity and frequent rain. At Baton Rouge, the average annual temperature is 68°F, and the average annual rainfall is about 60 in. (National Oceanic and Atmospheric Administration, 1995, p. 5, 8). With the exception of the Baton Rouge metropolitan area, much of the study area is rural and agricultural.

## Hydrogeologic Setting

Beneath the study area is a sequence of complexly interbedded, interconnected, lenticular, alluvial, freshwater-bearing, sandy, and graveliferous strata that form a wedge of sediment that dips and thickens in a south-to-southwest direction. Fourteen freshwater aquifers (fig. 2) in the area are composed of sediment that can contain very fine to coarse sand and pea- to cobble-size gravel (Meyer and Turcan, 1955, p. 13-47). Thirteen of the aquifers were originally named according to their general depth in the Baton Rouge industrial district (Meyer and Turcan, 1955, p. 13). A prominent hydrogeologic feature in the region is the Baton Rouge fault (fig. 1) which extends from east of the study area, through East and West Baton Rouge Parishes, to west of the study area (Durham and Peeples, 1956; Murray, 1961, p. 188-190; McCulloh, 1991, p. 1-20).

Precipitation in the northern part of the study area and north of the study area in Mississippi is the primary source of recharge of freshwater to the "1,200-foot" sand. Because the aquifers in the region are interconnected, some infiltrated precipitation percolates down into and through the surficial aquifers in the recharge area to deeper interconnected aquifers, which include the "1,200-foot" sand (Morgan, 1963, p. 11-13). Generally, water continues to move down in a southerly direction through the aquifer toward the Baton Rouge fault at rates that range from a few tens of feet per year to several hundreds of feet per year (Buono, 1983, p. 24). The southern limit of freshwater in the "1,200-foot" sand generally is considered to be at or near the Baton Rouge fault (Tomaszewski, 1996, p. 6).

Development of the "1,200-foot" sand increased substantially after 1953 (Morgan, 1961, p. 36; Kazmann, 1970, fig. 9). From 1943 to 2001, water levels declined about 140 ft at well WBR-5 (fig. 3). Well WBR-5 is located near pumping centers in the Baton Rouge industrial district (fig. 4). However, from 1961 to 2001, water levels at well EF-6 changed less than 25 ft (fig. 3). Although both wells are screened in the "1,200-foot" sand, well EF-61 is located near the recharge area and where little or no water withdrawals occur.

Before development, water entered the "1,200-foot" sand in the recharge area, and flowed generally in a south to southwest direction to the discharge area near the Baton Rouge fault (Meyer and Turcan, 1955, p. 51; Morgan, 1963, p. 13). At the discharge area, the Baton Rouge fault can act as a leaky barrier to horizontal ground-water flow (Whiteman, 1979, p. 12, 13). Also, water from the recharge area would move upward (probably along the fault) from the "1,500-foot" sand into the "1,200-foot" sand and from the "1,200-foot" sand into the "1,000-

<sup>1</sup>Saltwater in this report is defined as water that contains chloride at concentrations of more than 250 mg/L. Concentrations of chloride greater than 250 mg/L exceed the Secondary Maximum Contaminant Level (SMCL) for drinking water (U.S. Environmental Protection Agency, 1977, 1992). SMCLs are established for contaminants that can adversely affect the aesthetic quality of drinking water. At high concentrations or values, health implications as well as aesthetic degradation may also exist. SMCLs are not federally enforceable, but are intended as guidelines for the states.

## CONVERSION FACTORS, DATUMS, AND ABBREVIATED WATER-QUALITY UNIT


Multiply	By	To obtain
inch (in.)	25.4	millimeter (mm)
foot (ft)	0.3048	meter (m)
foot per year (ft/yr)	0.3048	meter per year (m/yr)
mile (mi)	1.609	kilometer (km)
square mile (mi <sup>2</sup> )	2.590	square kilometer (km <sup>2</sup> )
gallons per minute (gal/min)	0.06309	liter per square (L/s)
million gallons per day (Mgal/d)	3,785	cubic meter per day (m <sup>3</sup> /d)

Temperature in degrees Fahrenheit (°F) can be converted to degrees Celsius (°C) as follows: °C = (°F - 32)/1.8.

Vertical coordinate information in this report is referenced to the National Geodetic Vertical Datum of 1929 (NGVD 29)—a geodetic datum derived from a general adjustment of the first-order level nets of both the United States and Canada, formerly called Sea Level Datum of 1929.

Horizontal coordinate information in this report is referenced to the North American Datum of 1927.

Abbreviated water-quality unit:  
milligrams per liter (mg/L)



Base map modified from Louisiana Oil Spill Coordinator, Office of the Governor, Louisiana GIS CD: A Digital Map of the State, Version 2.0

Figure 1. Water withdrawals from the "1,200-foot" sand and location of the study area in the Baton Rouge area, southeastern Louisiana, 2001.

foot" sand due to vertical head<sup>2</sup> differences at the discharge area (Meyer and Turcan, 1955, p. 51; Morgan, 1963, p. 13). Recently, however, water withdrawals in the study area have caused water to flow toward pumping centers and reduced the vertical head gradient in what was the discharge area near the fault, and the upward movement of water has diminished (Meyer and Turcan, 1955, p. 51; Morgan, 1963, p. 13).

Large water withdrawals north of the fault might have induced saltwater encroachment from south of the fault toward pumping centers north of the fault where the "1,200-foot" sand previously contained freshwater (Tomaszewski, 1996, p. 36). Chloride concentrations above background levels (10 mg/L) were detected in water from well EB-621 (figs. 4, 5) from 1978 to 1988 and in 1992 (Tomaszewski and Anderson, 1995, table 6). Tomaszewski (1996, fig. 20) shows a 0.5-mi<sup>2</sup> area of saltwater at well EB-621 in the vicinity of Jefferson Highway at Interstate 12 in Baton Rouge. Tomaszewski (1996, p. 36) states that the increased chloride concentration might be due to upconing of saltwater from the base of the aquifer during pumping or leakage of saltwater across the fault.

<sup>2</sup>The altitude to which water rises (in a well) at a given point as a result of reservoir pressure (Bates and Jackson, 1984, p. 231).

System	Series	Stratigraphic unit	Aquifer <sup>3</sup> or confining unit
Quaternary	Holocene	Mississippi River and other alluvial deposits	Mississippi River alluvial aquifer
	Pleistocene	Unnamed Pleistocene deposits	Shallow sands Upland terrace aquifer "400-foot" sand "600-foot" sand
Tertiary	Pliocene	Blounts Creek Member	"800-foot" sand
			"1,000-foot" sand
			"1,200-foot" sand
	? (Miocene)	Fleming Formation	"1,500-foot" sand
			"1,700-foot" sand
			Castor Creek Member
Miocene	Williamson Creek Member	"2,000-foot" sand	
		Dough Hills Member	"2,400-foot" sand
? (Oligocene)	Carnahan Bayou Member	"2,800-foot" sand	
		Lena Member	Unnamed confining unit
? (Oligocene)	Catahoula Formation	Catahoula aquifer	

<sup>3</sup>Clay units separating aquifers in the Baton Rouge area are discontinuous and unnamed.

Figure 2. Hydrogeologic units in the Baton Rouge area, southeastern Louisiana (modified from Stuart and others, 1994, fig. 5; Lovelace and Lovelace, 1995, fig. 1).





Figure 3. Water withdrawals from the "1,200-foot" sand and water levels in wells WBR-5 and EF-61 in the Baton Rouge area, southeastern Louisiana.

## Louisiana Ground-Water Map No. 15:

### Potentiometric Surface of the "1,200-Foot" Sand of the Baton Rouge Area, Louisiana, Spring 2001

By

Jason M. Griffith and John K. Lovelace

2003



For additional information, contact:  
District Chief  
U.S. Geological Survey  
3535 S. Sherwood Forest Blvd., Suite 120  
Baton Rouge, LA 70816  
E-mail: dc\_la@usgs.gov  
Fax: (225) 298-5490  
Telephone: (225) 298-5481  
Home page: <http://la.water.usgs.gov>

Copies of this report can be purchased from:  
U.S. Geological Survey  
Branch of Information Services  
Box 25286  
Denver, CO 80225  
E-mail: [infoservices@usgs.gov](mailto:infoservices@usgs.gov)  
Fax: (303) 202-4188  
Telephone (toll free): 1-888-ASK-USGS

### Acknowledgments

The authors gratefully acknowledge the assistance and cooperation of numerous public water suppliers, industrial facilities, and private well owners who allowed water levels to be measured in their wells. A special thanks is given to Don C. Dial, Director, Capital Area Ground Water Conservation Commission, for his support and assistance during the preparation of this report.

### POTENTIOMETRIC SURFACE


Potentiometric-surface maps (figs. 4, 5) were constructed using water-level data from 25 wells completed in the "1,200-foot" sand (table 1). Water levels were measured during April and May 2001. Water levels were measured using steel or electrical tapes marked with 0.01-ft gradations. Wells in which water levels were measured were not being pumped at the time the measurements were made. If wells recently were pumped, water levels were measured after an appropriate recovery period. Water levels were not measured south of the Baton Rouge fault where the aquifer is offset and hydraulically separated from its equivalent unit north of the fault.

The highest water level, 154.19 ft above NGVD 29, was measured at well WF-169 in northern West Feliciana Parish (table 1). The lowest water levels of more than 90 ft below NGVD 29 were measured at wells EB-580 and EB-946 in the industrial district (table 1, fig. 5). Water levels were more than 50 ft below NGVD 29 in most of the Baton Rouge metropolitan area. A small cone of depression about 5 ft above NGVD 29 was noted at well PC-180 in eastern Pointe Coupee Parish. Another cone of depression about 95 ft below NGVD 29 was located at well EB-946. A comparison between the 1990 (Tomaszewski, 1996, p. 37) and the 2001 potentiometric-surface maps of the "1,200-foot" sand indicates water levels in the Baton Rouge metropolitan area declined about 20 ft during the 11-year period.

In spring 2001, the flow of water in the "1,200-foot" sand in the Baton Rouge area generally was down gradient from the recharge area toward pumping centers along the Mississippi River and in Baton Rouge (figs. 1, 4, 5). In East and West Feliciana Parishes, flow generally was south to southwest toward Baton Rouge. In East and West Baton Rouge and southeastern Pointe Coupee Parishes, flow was radial toward the industrial district.

### SELECTED REFERENCES


- Bates, R.L., and Jackson, J.A., eds., 1984, Dictionary of geological terms (3d ed.); New York, Doubleday, 571 p.
- Buono, Anthony, 1983, The Southern Hills regional aquifer system of southeastern Louisiana and southwestern Mississippi: U.S. Geological Survey Water-Resources Investigations Report 83-4189, 38 p.
- Calhoun, Milburn, and Frois, Jeanne, eds., 1997, Louisiana almanac (1997-98 ed.); Gretna, La., Pelican Publishing Company, 695 p.
- Compton, R.R., 1985, Geology in the field: New York, John Wiley and Sons, p. 379.
- Durham, C.O., Jr., and Peeples, E.M. III, 1956, Pleistocene fault zone in southeastern Louisiana [abs.]: Transactions of the Gulf Coast Association of Geological Societies, v. 6, p. 65-66.
- Halford, K.J., and Lovelace, J.K., 1994, Analysis of ground-water flow in the "1,200-foot" aquifer, Baton Rouge area, Louisiana: Louisiana Department of Transportation and Development Water Resources Technical Report no. 54, 68 p.
- Huntzinger, T.L., Whiteman, C.D., Jr., and Knochenmus, D.D., 1985, Simulation of ground-water movement in the "1,500- and 1,700-foot" aquifer of the Baton Rouge area, Louisiana: Louisiana Department of Transportation and Development, Office of Public Works Water Resources Technical Report no. 34, 52 p.
- Kazmann, R.G., 1970, The present and future ground-water supply of the Baton Rouge area: Louisiana State University, Louisiana Water Resources Research Institute Bulletin 5, 44 p.
- Lovelace, J.K., and Lovelace, W.M., 1995, Hydrogeologic unit nomenclature and computer codes for aquifers and confining units in Louisiana: Louisiana Department of Transportation and Development Water Resources Special Report no. 9, 12 p.
- McCulloh, R.P., 1991, Surface faults in East Baton Rouge Parish: Louisiana Geological Survey Open-File Series 91-02, 25 p.
- Meyer, R.R., and Rollo, J.R., 1965, Saltwater encroachment, Baton Rouge area, Louisiana: Department of Conservation, Louisiana Geological Survey, and Louisiana Department of Public Works Water Resources Pamphlet no. 17, 9 p.
- Meyer, R.R., and Turcan, A.N., Jr., 1955, Geology and ground-water resources of the Baton Rouge area, Louisiana: U.S. Geological Survey Water-Supply Paper 1296, 138 p.
- Morgan, C.O., 1961, Ground-water conditions in the Baton Rouge area, 1954-59, with special reference to increased pumpage: Department of Conservation, Louisiana Geological Survey, and Louisiana Department of Public Works Water Resources Bulletin no. 2, 78 p.
- \_\_\_\_\_, 1963, Ground-water resources of East Feliciana and West Feliciana Parishes, Louisiana: Louisiana Department of Public Works, 58 p.
- Murray, G.E., 1961, Geology of the Atlantic and Gulf Coastal Province of North America: New York, Harper and Bros., p. 188-191.
- National Oceanic and Atmospheric Administration, 1995, Climatological data annual summary—Louisiana: Asheville, N.C., Environmental Data Service, 23 p.
- Rollo, J.R., 1969, Saltwater encroachment in aquifers of the Baton Rouge area, Louisiana: Department of Conservation, Louisiana Geological Survey, and Louisiana Department of Public Works Water Resources Bulletin no. 13, 45 p.
- Tomaszewski, D.J., 1996, Distribution and movement of saltwater in aquifers in the Baton Rouge area, Louisiana, 1990-92: Louisiana Department of Transportation and Development Water Resources Technical Report no. 59, 44 p.
- Tomaszewski, D.J., and Anderson, M.L., 1995, Data from wells in a chloride monitoring network, Baton Rouge area, Louisiana, 1965-94: Louisiana Department of Transportation and Development Water Resources Basic Records Report no. 19, 40 p.
- U.S. Environmental Protection Agency, 1977, National secondary drinking water regulations: Federal Register, March 31, 1977, v. 42, no. 62, Public Law 143, p. 17143-17147.
- \_\_\_\_\_, 1992, Drinking water regulations and health advisories: Washington, D.C., U.S. Environmental Protection Agency, Office of Water, 11 p.
- Whiteman, C.D., Jr., 1979, Saltwater encroachment in the "600-foot" and "1,500-foot" sands of the Baton Rouge area, Louisiana, 1966-78, including a discussion of saltwater in other sands: Louisiana Department of Transportation and Development, Office of Public Works Water Resources Technical Report no. 19, 49 p.
- Winner, M.D., Jr., Forbes, M.J., Jr., and Broussard, W.L., 1968, Water resources of Pointe Coupee Parish, Louisiana: Department of Conservation, Louisiana Geological Survey, and Louisiana Department of Public Works Water Resources Bulletin no. 11, 110 p.



Base map modified from Louisiana Oil Spill Coordinator, Office of the Governor, Louisiana GIS CD: A Digital Map of the State, Version 2.0  
**Figure 4.** Potentiometric surface of the "1,200-foot" sand in the Baton Rouge area, southeastern Louisiana, spring 2001.

**Table 1.** Water-level data used to construct the potentiometric-surface map of the "1,200-foot" sand in the Baton Rouge area, southeastern Louisiana, spring 2001 [Well locations and numbers are shown in figures 4 and 5.]

Well number	Altitude of land surface, in feet above NGVD 29	Date measured	Water level, in feet above (+) or below (-) NGVD 29
<b>East Baton Rouge Parish</b>			
EB-146	52.00	4-14-01	-65.72
EB-327	55.00	4-12-01	-67.28
EB-523	59.00	4-25-01	-74.52
EB-580	65.00	4-30-01	-90.31
EB-679	40.00	4-25-01	-46.58
EB-752	49.00	5-17-01	-57.48
EB-840	95.00	4-19-01	+0.64
EB-925	40.00	4-20-01	-56.57
EB-946	59.00	5-1-01	-95.46
EB-990	44.00	4-20-01	-65.31
EB-1003	40.00	4-20-01	-56.90
EB-1016B	47.00	4-20-01	-77.16
EB-1153	72.00	4-27-01	-38.32
<b>East Feliciana Parish</b>			
EF-61	210.00	4-19-01	+123.89
<b>Livingston Parish</b>			
LI-204A	60.00	5-1-01	-17.71
<b>Pointe Coupee Parish</b>			
PC-169	33.00	5-3-01	+26.44
PC-179	22.00	4-20-01	+15.41
PC-180	30.00	5-3-01	+4.56
PC-288	41.00	5-3-01	+15.02
<b>West Baton Rouge Parish</b>			
WBR-5	27.00	4-25-01	-69.23
WBR-102A	18.00	4-25-01	-37.57
WBR-148	14.00	4-25-01	-35.24
<b>West Feliciana Parish</b>			
WF-151	190.00	4-11-01	+77.24
WF-169	262.00	4-12-01	+154.19
WF-266	125.00	4-6-01	+33.31



Base map modified from Louisiana Oil Spill Coordinator, Office of the Governor, Louisiana GIS CD: A Digital Map of the State, Version 2.0  
**Figure 5.** Potentiometric surface of the "1,200-foot" sand in parts of East and West Baton Rouge Parishes, southeastern Louisiana, spring 2001.

## Louisiana Ground-Water Map No. 15: Potentiometric Surface of the "1,200-Foot" Sand of the Baton Rouge Area, Louisiana, Spring 2001

By  
Jason M. Griffith and John K. Lovelace